



Decorative Paints and Coatings

Sandeco Art / Art Velvet

DESCRIPTION

SANDECO ART is an acrylic emulsion based, silver and gold pearlescent finished grainy metallic decorative coating.

SANDECO ART VELVET generally has the same features by also having the features of being more thinly grained and softer.

APPLICATION AREA

SANDECO ART is used on walls, plasters, exposed concrete and wooden surfaces in building interiors, after the surface preparation and with a suitable undercoat.

SURFACE PREPARATION

After cleaning all kinds of dirt, oil, blistered paint and dust from the application surfaces, surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR and painted surfaces should be primed with SAN DECO DECOPRIMER.

APPLICATION INSTRUCTIONS

- Once the undercoat is applied, with a wooden brush, apply SANDECO ART / SANDECO ART VELVET, without dilution. While it is still wet, apply a single layer with the wooden brush, by forming the desired patterns with circular or linear movements,
- SANDECO ART VELVET is applied same method like SANDECO ART. The only addition of application on to this is, shaving the final textures with plastic spatula before product dries.
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

DRYING TIME

Allow 4-5 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

-1 lt covers 6,5 – 8,5 m² of surface

-1 kg covers 5,0 – 6,5 m² of surface

-The paint consumption for 1 m² area is 120 – 160 ml and 150 - 200 gr.

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; during at a temperature between +5°C and +35°C.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Decorative Paints and Coatings

Sandeco Art / Art Velvet

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

**Product Technical Data Sheet No. DP.003.ENG - Rev00 March 2020**

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88