

Decorative Paints and Coatings Galaxy

DESCRIPTION

GALAXY is an acrylic emulsion based with flakes effected ready to use decorative paint system. With the texture of it, it provides modern and stylish finishes for any kind of environments where you will get the refined taste of delicacy.

APPLICATION AREA

GALAXY can be used for decorating interiors wall where it adds depth and character to all kinds of environments. It is used with suitable undercoat on walls, plasters, exposed concrete and wooden surfaces after surface preparation.

FEATURES

- A decorative materials for indoors,
- Creates an extraordinary old wall effect with its unique granular structure,
- Thanks to its transparent film, the color of the applied surface will not change,
- Resistant to rough and long-time abrasion. Resistant to mild chemicals,
- As it is water-based, it is harmless to human health and environment,
- It provides a pleasant odour in the application environments with its perfumed feature.

SURFACE PREPARATION

- After removing all kinds of dirt, grease, bloated paint and dust from the application surface, the surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR and undercoated with SAN DECO DECOPRIMER.
- Apply Decoprimer by diluting with 20-25% by volume fresh water and apply as 2 layers using brush or roller; and allow the layer to dry well.

APPLICATION INSTRUCTIONS

- Once the primer is dried, mix GALAXY well with spatula, than apply GALAXY to the surface using a special brush. Give the final appearance to the surface using a plastic spatula after waiting 25 minutes; it is possible to get various decorative effects depending on the application techniques,
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

DRYING TIME

Allow 4-5 hours for touch dry and 24-48 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

- -1 lt covers 6.5 8.0 m² of surface,
- -1 kg covers 6.0 7.5 m² of surface,
- -The paint consumption for 1 m^2 area is 125 150 ml and 130 165 gr.

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight at a temperature between +5°C and +35°C.



Decorative Paints and Coatings Galaxy

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product



Product Technical Data Sheet No. DP.009.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.