



Decorative Paints and Coatings

Amarsis Primer

DESCRIPTION

AMARSIS PRIMER is an acrylic emulsion based, special primer with high covering capability, formulated as coloured primer for AMARSIS. Amarsis Dark Primer (dark grey) and Amarsis Light Primer (light grey) are two types.

APPLICATION AREA

It is applied on mineral surfaces such as all kinds of concrete, gaseous concrete, pressed brick, thin plaster and limestone plaster.

SURFACE PREPARATION

After removing all kinds of dirt, grease, bloated paint and dust from the application surface, the surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR.

APPLICATION INSTRUCTIONS

- Before application, AMARSIS PRIMER should be mechanically mixed until it became homogenous after diluting for 5-10% in volume with clean water and then applied with roller as one layer.
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

DRYING TIME

Allow 2-3 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

-1 lt covers 12,0 – 14,5 m² of surface

-1 kg covers 7,5 – 9,5 m² of surface

-The paint consumption for 1 m² area is 70-80 ml and 110-130 gr.

STORAGE

It should be stored for in a sealed package, cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Decorative Paints and Coatings

Amarsis Primer

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. DP.012.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88