



Decorative Paints and Coatings

Decostucco

DESCRIPTION

DECOSTUCCO is an acrylic emulsion based; containing various types of quartz, limestone and pigments; at the paste consistency; given texture and form with trowel or spatula; glossy finished interior wall coating material.

APPLICATION AREA

Used after surface preparation with the appropriate primer on wall, plaster coating, concrete and wood surfaces.

SURFACE PREPARATION

After removing all kinds of dirt, grease, bloated paint and dust from the application surface, the surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR and undercoated with SAN DECO DECOPRIMER.

APPLICATION INSTRUCTIONS

- DECOSTUCCO should well mixed before application
- One layer DECOSTUCCO is applied to the surface with a stainless steel trowel, the second coat is applied if the desired smoothness and coverage is not obtained.
- Once the product is dried after 24 hours, the surface is sanded with fine sandpaper and the desired effect is applied by trowel or spatula. To make the surface more glossy, steel trowel work can be done over again.
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

DRYING TIME

Allow 2-3 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

The consumption depending on the surface smoothness, its porosity and the application methods is:

-1 lt covers 2,85 – 4,30 m² of surface

-1 kg covers 1,65 – 2,50 m² of surface

-The paint consumption for 1 m² area is 230 – 350 ml and 400 – 600 gr.

STORAGE

It should be stored in a sealed package, cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Decorative Paints and Coatings

Decostucco

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. DP.014.ENG - Rev01 November 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88