



Decorative Paints and Coatings

Nostalgie Base

DESCRIPTION

NOSTALGIE BASE is an acrylic-based emulsion; a fibre-reinforced decorative interior coating

APPLICATION AREA

It is used with a suitable primer after the surface preparation on the walls, plasters, exposed concretes and wooden surfaces in the buildings' interiors.

SURFACE PREPARATION

After cleaning all kinds of dirt, oil, swollen paint and dust on the surfaces to be applied, the surface defects should be corrected by SAN DECO ACRYLIC PUTTY INTERIOR and primed by SAN DECO DECOPRIMER

APPLICATION INSTRUCTION

- Before the application, NOSTALGIE BASE should be properly mixed without thinning
- NOSTALGIE BASE should be applied irregularly on the surface with a plastic or a steel trowel, according to the desired effect
- Two days after having applied NOSTALGIE BASE, sand the surface with sand paper and apply NOSTALGIE FINISH on the surface with circular movements with its special cloth or gloves.
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

DRYING TIME

Allow 6-8 hours for touch dry and 48 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

- 1 lt covers 1,0 - 1,5 m² of surface
- 1 kg covers 0,8 - 1,0 m² of surface
- The paint consumption for 1 m² area is 650-1000 ml and 1000-1175 gr.

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88



Decorative Paints and Coatings

Nostalgie Base

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. DP.015.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88