



Decorative Paints and Coatings

Effect Finish

DESCRIPTION

EFFECT FINISH is a half mat decorative final coat paint with consisting of the special acrylic resin mixture. It is the product for application on the MIRZASTO product and it compose metallic and reflective look.

APPLICATION AREA

It is applied on wall, plaster, exposed concrete and wooden surfaces as final coat.

FEATURES

- It makes the applied surfaces looks like metallic and glittering,
- It does not change the pattern and design of MIRZASTO product and can be applied easlily,
- It can be wiped with water,
- Due its high vapor permeability, it allows surface to discharge the steam and breathe,
- As it is water-based, it is harmless to human health and environment,
- It provides a pleasant odor in the application environments with its perfumed feature.

SURFACE PREPARATION

After cleaning all kinds of dirt, oil, blistered paint and dust from the application surfaces, surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR, and painted surfaces should be primed with SAN DECO DECOPRIMER.

APPLICATION INSTRUCTIONS

- EFFECT FINISH is a product should be applied the product of MIRZASTO. After 4-5 hours (23±2°C) later MIRZASTO is applied according to its instructions, application process of EFFECT FINISH can start,
- EFFECT FINISH product can be applied with plastic or steel trowel without thinning the product. Allow 2 hours between each coat,
- In EFFECT FINISH application; in order to demonstrate MIRZASTO product's design and patterns more obvious, product roughness on surface must be taken out with steel trowel,
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

DRYING TIME

Allow 2-3 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity and application methods, for a single coat application;

-1 lt covers 16,0 – 20,0 m² of surface

-1 kg covers 15,7 – 19,7 m² of surface

-The paint consumption for 1 m² area is 50 - 62,5 ml and 50 - 65 gr.

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight a temperature between +5°C and +35°C.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Decorative Paints and Coatings

Effect Finish

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. DP.022.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88