



Decorative Paints and Coatings

Crackie

DESCRIPTION

CRACKIE is a water based transparent cracking varnish that gives a cracked effect at the same time creates a modern look in interiors.

APPLICATION AREA

Used on wall, plaster coating, concrete and wood surfaces after surface preparation with the appropriate primer.

FEATURES

- Antique look environments can be achieved with cracking patterns
- Due its high vapor permeability, it allows surface to discharge the steam and breathe
- As it is water-based, it is harmless to human health and environment.

SURFACE PREPARATION

After cleaning all kinds of dirt, oil, blistered paint and dust from the application surfaces, surface defects should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR, and painted surfaces should be primed with SAN DECO DECOPRIMER.

APPLICATION INSTRUCTIONS

- After Decoprimer application is completely dried, desired color matt or semi matt paint can be applied as 2 layer with roller by also thinning it with clean water. Between each coat, there should be 2 hours waiting period. CRAKIE should be applied from top to the bottom equally without thinning the application on the surface. According to the weather conditions ($23\pm 2^{\circ}\text{C}$) there should be 3-4 hours waiting period. In the condition of wheather changes drying period may vary. Before the last coat applied CRAKIE application must be checked as if there is any sticking or not. If there is not sticking, last coat application can be done.
- Last coat mat or semi mat paint which is chosen with different color than first one, should be applied by thinning with water and applying equally to the surface. Spreading of the product should be done carefully and homogeneously as patterns may be changed.
- Product should be applied in narrow surfaces
- The temperature of the application environment must be kept between $+5^{\circ}\text{C}$ and $+35^{\circ}\text{C}$ during application and for 24 hours afterwards.

DRYING TIME

Allow 3-4 hours for touch dry and check for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity and application methods, for a single coat application:

-1 lt covers 10,0 – 12,5 m² of surface

-1 kg covers 8,5 – 10,0 m² of surface

-The paint consumption for 1 m² area is 80-100 ml and 100-120 gr.

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight at a temperature between $+5^{\circ}\text{C}$ and $+35^{\circ}\text{C}$.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Decorative Paints and Coatings

Crackie

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. DP.031.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88