

DESCRIPTION

Decorative final coat paint consist of mixtures of special acrylic resins applied on decorative putty, paint and other decorative products like putty consistency to provide a metallic and reflective pearlescent and glitter effect.

APPLICATION AREA

Applied as topcoat paint on decorative products applied following the surface preparation on walls, plaster, gross concrete and timber surfaces.

SURFACE PREPARATION

After cleaning all kinds of dust, dirt, oil, swelled paint from application area, surface irregularities should be eliminated by SAN DECO ACRYLIC PUTTY INTERIOR and should be undercoated with SAN DECO DECOPRIMER

APPLICATION INSTRUCTION

- While applying DECORATIVE FINISH on decorative paste and on other decorative products of putty density, using a trowel or a special brush is suggested. If it is to be applied on paint type products, then using a roller or a brush is recommended.
- While applying DECORATIVE FINISH with a trowel, it should not be diluted; but the application convenience should be ensured by thinning when it is to be applied with roller, brush or sponge.
- During the application and for 24 hours after application medium temperature should be kept at least at +5 °C, and at most +35 °C.

DRYING TIME

Contact time at 23°C' is reached after about 2-3 hours while complete drying is reached in 24 hours.

THEORETICAL CONSUMPTION

Consumption may vary depending on surface smoothness, absorbency and application techniques and on the product to be applied on the sub-surface. Theoretical consumption for single coat;

Arona Consumption

Paint consumption for 1 m² area 95 - 145 ml and 100 - 150 g,

Lanom Consumption

Paint consumption for 1 m² area 92 - 140 ml and 100 - 150 g,

Flam Consumption:

Paint consumption for 1 m² area 75 - 115 ml and 80- 120 g,

PEARLSCENT DECORATIVE FINISH

Pearlescent Topcoat Paint Consumption:

Paint consumption for 1 m² area 95 - 155 ml and 100- 160 g,

Glitter Topcoat Paint Consumption:

Paint consumption for 1 m² area 50 - 65 ml and 50 - 65 g.

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; and at a temperature between +5 °C and +35 °C.

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1) May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product