



## Interior Products Range

# Uniprimer

### DESCRIPTION

UNIPRIMER is acrylic emulsion based, filled interior and exterior primer.

### APPLICATION AREA

It is used as the primer of acrylic based paint and plaster material applied on mineral surfaces such as any type of concrete, aerated concrete, pressed bricks or finishing coat.

### FEATURES

- Prevents the absorbing capacity of the surface it is applied; thus reduces the consumption of paint,
- It has high adhesive feature,
- Serves as a connecting bridge between the final coating and the surface on mineral surfaces such as any type of concrete, aerated concrete, pressed bricks or finishing coat and surfaces with dusting behaviour and high absorption qualities such as satin plaster or plasterboard,
- It may be tinted with desired colour if it is required,
- As it is water-based, it is harmless to human health and environment.

### SURFACE PREPARATION

Once the dirt, grease, swollen paint and dust on the surface is cleaned, any roughness on the surface should be corrected with ACRYLIC PUTTY INTERIOR or EXTERIOR.

### APPLICATION INSTRUCTIONS

- Before application UNIPRIMER shall be diluted with clean water of 20-25% by volume and mixed well.
- Then It should be applied as a single coat with a roller, brush or spraying system,
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

### DRYING TIME

Allow 4-5 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

### THEORETICAL CONSUMPTION

#### UNIPRIMER CONSUMPTION

Depending on surface smoothness, porosity and application methods, for a single coat application;

-1 lt covers 14,5– 16,5 m<sup>2</sup> of surface,

-1 kg covers 9,5 – 11,5 m<sup>2</sup> of surface,

-The paint consumption for 1 m<sup>2</sup> area is 60 -70 ml and 85-105 gr.

### STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

**DEKA BOYA SANAYİ ve TİC. A.Ş.**



# Interior Products Range

## Uniprimer

### HAZARD STATEMENTS

**H317** May cause an allergic skin reaction.

### PRECAUTIONARY STATEMENTS

**P261** Avoid breathing dust/fume/gas/mist/vapours/spray.

**P272** Contaminated work clothing should not be allowed out of the workplace.

**P280** Wear protective gloves/protective clothing/eye protection/face protection.

**P302 + P352** IF ON SKIN: Wash with plenty of soap and water.


**P333 + P313** If skin irritation or rash occurs: Get medical advice/attention.

**P363** Wash contaminated clothing before reuse.

**EUH208** Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product



#### Product Technical Data Sheet No. IP.007.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

**This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.**

#### DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56  
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88