



## Interior Products Range

# Acrylic Primer 1X7

**DESCRIPTION**

ACRYLIC PRIMER 1X7 is an acrylic emulsion based concentrated primer with high penetration and adherence features.

**APPLICATION AREA**

ACRYLIC PRIMER 1X7 is applied on gypsum, whitewash, surfaces with low quality absorbing latex paint that lost its characteristic and surfaces with high absorption and/or chalking characteristic like aerated concrete etc.

**FEATURES**

- ACRYLIC PRIMER 1X7 prevents the absorbency of the surface, and decreases paint wastage/consumption,
- Serves as a binding bridge between the final coat of paint and the surface in mineral surfaces like all kind of concrete, aerated concrete, pressed brick, thin plaster and chalking surfaces like satin plaster, plaster board,
- Prevents early drying of the paint and prevents the colour waving that might occur on the final coat of paint on surfaces with different absorption,
- As it is water-based, it is harmless to human health and environment.

**SURFACE PREPARATION**

Clean all dirt, oil, blistered paint and dust off the application surface; level the surface defects with SAN DECO Acrylic Putty Interior.

**APPLICATION INSTRUCTIONS**

- Before application, one unit ACRYLIC PRIMER 1X7 should be diluted with 7 parts of water and mixed thoroughly.
- After dilution, primer application can be carried on,
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

**DRYING TIME**

Allow 4-5 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

**THEORETICAL CONSUMPTION**

Depending on surface smoothness, porosity and application methods, for a single coat application;

-1 lt covers 16,5– 20,0 m<sup>2</sup> of surface,

-1 kg covers 16,5– 20,0 m<sup>2</sup> of surface,

-The paint consumption for 1 m<sup>2</sup> area is 50 -60 ml 50 - 60 gr.

**STORAGE**

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

**DEKA BOYA SANAYİ ve TİC. A.Ş.**



Interior Products Range

# Acrylic Primer 1X7

**HAZARD STATEMENTS**

**H317** May cause an allergic skin reaction.

**PRECAUTIONARY STATEMENTS**

**P261** Avoid breathing dust/fume/gas/mist/vapours/spray.

**P272** Contaminated work clothing should not be allowed out of the workplace.

**P280** Wear protective gloves/protective clothing/eye protection/face protection.

**P302 + P352** IF ON SKIN: Wash with plenty of soap and water.

**P333 + P313** If skin irritation or rash occurs: Get medical advice/attention.

**P363** Wash contaminated clothing before reuse.

**EUH208** Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)  
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

**Product Technical Data Sheet No. IP.008.ENG - Rev00 March 2020**

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

**This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.**

**DEKA BOYA SANAYİ ve TİC. A.Ş.**

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56  
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88